

Electronic Multi-Channel Datalogger

for Current, Voltage, or Temperature Inputs



measuring
•
monitoring
•
analyzing

ZLS-2



- Graphic LCD Display, Backlight
- Input: 4...20 mA, 0 - 5 (10)V, Pt 100, Pt 500, Pt 1000
- 8 Channel Input
- 2 Switching Outputs
- Four Presentation Modes
- Interface RS 485, Modbus RTU, USB
- Sensor Power Supply
- Fully Scalable



KOBOLD companies worldwide:

ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECH REPUBLIC, EGYPT, FRANCE, GERMANY, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, UNITED KINGDOM, USA, VIETNAM

KOBOLD Instruments, Inc.
1801 Parkway View Drive
Pittsburgh, PA 15205
Main Office:
1.800.998.1020
1.412.788.4890
info@koboldusa.com
www.koboldusa.com

Description

The KOBOLD model ZLS is designed to record and display current values and technological parameters in the form of graphs. The device is equipped with 8 temperature (Pt100, Pt500, Pt1000) , current 4 - 20mA, 0 - 5 (10)V inputs and one digital input for controlling the recording process. It has a 8 MB memory, provides a maximum of 3000000 data recordings. The internal analog-digital converter has a 12 bit resolution, which provides high recording resolutions. Additionally, individual alphanumeric description (text) of each of the recorded channels is possible. The menu with full text description makes the unit easy to configure. However, due to a significant number of configured parameters, it is advisable to use the attached configuration software for PCs.



Functions

- 1, 4 or 8 Channel Input
- Input: TC + RTD or mA + V
- Data Memory: 3,000,000 Data Recordings
- Digital Input
- 2 Switching Outputs
- Interface: RS485, Modbus RTU
- USB Front Port for Flash Data Storage

Technical Details

Display:	Graphic LCD (128x64 Points), with Backlight
Measuring Range:	±9999 plus Decimal Point (Current Input) -148...1,112 °F (Temperature Input)
Measuring Inputs:	1, 4, or 8 Channel Pt 100, Pt 500, Pt 1000 (2- and 3-wire Connection) or 4 -20 mA, 0 - 5 (10)V Inputs, Common Grounding
Current Input Resistance:	100 Ω
Memory Capacity:	8 MB (3,000,000 Data Recordings)
Recording Interval:	1 s... 1 h

Additional Inputs: 1x Digital Input 24 V_{DC}

Note: Some USB pen drives are not supported by the ZLS because of different controllers. Memory sticks approved by KOBOLD are available on request.

Switching Outputs: 2 Electronic N/C Contacts
24 V_{AC/DC}, Max. 200 mA,
Short-circuit Proof

Supply Voltage: 19-50 V_{DC} or
85-260 V_{AC/DC}

Power Consumption: Typical: 7 VA
Max. 12 VA

Sensor Supply: 24 V_{DC} ±5% / 200 mA,
(Not Separated from Measuring)

Communication Interface: RS485, Galvanically Separated +
USB

Transmission Protocol: Modbus RTU

Transmission Speed: 1,200 - 115, 200 bit/s

Working Temperature: 32...140 °F

Storage Temperature: 14...158 °F

Humidity: Up to 90% without Condensation

Case Dimensions: 3.8" x 3.8" x 4.25" (W x H x D)

Panel Cut-out Dimensions:

3.56" x 3.56"

Installation Depth: Minimum of approx. 4.0"

Board Thickness: Max. 0.20"

Case: Board

Case Material: Plastic

Protection: IP40

IP54 (when Door is Installed,
Accessory Model ZLS-ZDK42)
IP20 Rear Side

Connection: Screw Terminal

Weight: Approx. 0.88 lbs



Order Details (Example: **ZLS-21A0UW4P**)

Model	Number of Channels	Input Signal	Power Supply	Additional Input Signal	Housing Version/Protection
ZLS-2..	..1.. = 1 Channel ..4.. = 4 Channels ..8.. = 8 Channels	..A.. = 4-20 mA, 0-5(10) V ..P.. = Pt100, Pt500, Pt1000	..0.. = 85-260 V _{AC/DC} ..3.. = 19-50 V _{DC}	..UW4.. = 1x Digital and USB	..P = Front IP40
Accessories					
ZLS-Z USB RS4 A	Converter Module USB-RS485, Weight: 0.29 lbs				
ZLS-Z RS2 RS4	Converter Module RS232 - RS485, Weight: 0.44 lbs				
ZLS-Z DK42	Transparent Door with Lock for DIN Housing (Protection IP54)				

Software Included

- **Toolkit:** PC software for data logger, easy configuring
- **Loggy Soft:** PC software for moving, reporting, archiving and displaying recorded data

Following Options are Available on Request:

- USB Host Port on Read Side
- IP65 Protection Class
- Extended Working Temperature Range from -4...122 °F

Dimensions

