



NBK-M Application Guide

Rev 06/26/2024

General Information

Contact Name: _____

Date: _____

Company Name: _____

Part Number: _____

Phone: _____

Number of Pieces Required: _____

Email: _____

Quote Number (if already quoted): _____

This has not been quoted yet and pricing is required.

Design Conditions


1. Pressure: Normal: _____ PSIG Maximum: _____ PSIG

2. Temperature: Normal: _____ °F Maximum: _____ °F

3. Liquid Type: _____

4. Liquid Specific Gravity at Normal Operating Temp: _____ at Maximum Temp: _____

5. Liquid Viscosity at Normal Operating Temperature: _____



Mounting Configuration

1. Measuring Length "M": _____ Inches cm (M = Center to Center Length between Fittings)

2. Fitting Size: 1/2" 3/4" 1"

3. Fitting Type: NPT Thread 150 LB ANSI Flange 300 LB ANSI Flange Other: _____

Indicator

Polypropylene (250 °F Max. - Option "P")

Ceramic (390 °F Max. - Option "K")

None (Option "0")

Custom Configurations / Special Requirements

NBK Purchasing Process

In order to provide you with the correct and most cost-effective NBK, our technical team at KOBOLD will partner with you in building your NBK. NBKs are highly customizable, have critical nuances that are easy to overlook, and are built to order. After submission of this form, one of our engineers will contact you to schedule a consultation. If you are a distributor or reseller, please consider including any end-users in that consultation who will be part of the design and installation. This will shorten the purchasing process and ensure that nothing is overlooked along the various stakeholders in the supply chain. If you require immediate assistance or have any questions, please contact our engineering team at 412-788-2830. Please email this form to info@koboldusa.com.